

Micro Focus

Fortify WebInspect Agent

Software Version: 20.1.0
For use with Fortify WebInspect 20.1.0

Installation Guide

Document Release Date: May 2020
Software Release Date: May 2020

Legal Notices

Micro Focus
The Lawn
22-30 Old Bath Road
Newbury, Berkshire RG14 1QN
UK

<https://www.microfocus.com>

Warranty

The only warranties for products and services of Micro Focus and its affiliates and licensors ("Micro Focus") are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Micro Focus shall not be liable for technical or editorial errors or omissions contained herein. The information contained herein is subject to change without notice.

Restricted Rights Legend

Confidential computer software. Except as specifically indicated otherwise, a valid license from Micro Focus is required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Copyright Notice

© Copyright 2014 - 2020 Micro Focus or one of its affiliates

Trademark Notices

All trademarks, service marks, product names, and logos included in this document are the property of their respective owners.

Documentation Updates

The title page of this document contains the following identifying information:

- Software Version number
- Document Release Date, which changes each time the document is updated
- Software Release Date, which indicates the release date of this version of the software

This document was produced on May 07, 2020. To check for recent updates or to verify that you are using the most recent edition of a document, go to:

<https://www.microfocus.com/support-and-services/documentation>

Contents

Preface	5
Contacting Micro Focus Fortify Customer Support	5
For More Information	5
About the Documentation Set	5
 Change Log	 6
 Installing the WebInspect Agent	 7
Installing the Java Agent	7
Getting Started with the Java Agent Installation	7
Overview of Java Agent Installation	8
Installing the Java Agent	8
Adding the Agent to an Application Server or Service Running Java	10
Adding the Agent to a Standalone Apache Tomcat Server	10
Adding the Agent to an Apache Tomcat Windows Service	11
Adding the Agent to an IBM WebSphere Server Using the Server Administrative Console	12
Adding the Agent to an IBM WebSphere Server Using wsadmin	13
Adding the Agent to a Red Hat JBoss Server	14
Adding the Agent to an Oracle WebLogic Server	18
Adding the Agent to a System Service	19
Adding the Agent to a Standalone Java Application	20
Adding the Agent to a Host Machine That Has More Than One Protected Application	20
Verifying the Java Agent Installation	22
Troubleshooting Tips for the Java Agent	22
Uninstalling a Java Agent	22
Installing the .NET Agent	23
Getting Started with the .NET Agent Installation	23
Overview of .NET Agent Installation	23
Installing the .NET Agent	24
Silent Install	25

Verifying the .NET Agent Installation	25
Restarting IIS and Viewing the New .NET Agent	25
Troubleshooting Tips for the .NET Agent	26
Uninstalling a .NET Agent	26
Restarting IIS and Viewing the New .NET Agent	26
Send Documentation Feedback	28

Preface

Contacting Micro Focus Fortify Customer Support

You can contact Micro Focus Fortify Customer Support, manage your Support cases, acquire licenses, and manage your account on the following website:

<https://softwaresupport.softwaregrp.com>

For More Information

For more information about Fortify software products:

<https://software.microfocus.com/solutions/application-security>

About the Documentation Set

The Fortify Software documentation set contains installation, user, and deployment guides for all Fortify Software products and components. In addition, you will find technical notes and release notes that describe new features, known issues, and last-minute updates. You can access the latest versions of these documents from the following Micro Focus Product Documentation website:

<https://www.microfocus.com/support-and-services/documentation>

Change Log

The following table lists changes made to this document. Revisions to this document are published only if the changes made affect product functionality.

Software Release / Document Version	Change
20.1.0	Updated: Release information. Fixed: Verifying the Java Agent Installation section.
19.2.0	Updated: Release information.
19.1.0	Updated: Release information.
18.4	Updated: Minor version and branding updates.

Installing the WebInspect Agent

To install the agent, go to one of the following sections:

["Overview of Java Agent Installation" on the next page](#)

["Overview of .NET Agent Installation" on page 23](#)

Installing the Java Agent

Topics covered in this section:

Getting Started with the Java Agent Installation	7
Overview of Java Agent Installation	8
Installing the Java Agent	8
Adding the Agent to an Application Server or Service Running Java	10
Adding the Agent to a Standalone Apache Tomcat Server	10
Adding the Agent to an Apache Tomcat Windows Service	11
Adding the Agent to an IBM WebSphere Server Using the Server Administrative Console	12
Adding the Agent to an IBM WebSphere Server Using wsadmin	13
Adding the Agent to a Red Hat JBoss Server	14
Adding the Agent to an Oracle WebLogic Server	18
Adding the Agent to a System Service	19
Adding the Agent to a Standalone Java Application	20
Adding the Agent to a Host Machine That Has More Than One Protected Application	20
Verifying the Java Agent Installation	22
Troubleshooting Tips for the Java Agent	22
Uninstalling a Java Agent	22

Getting Started with the Java Agent Installation

Topics covered in this section:

Overview of Java Agent Installation	8
Installing the Java Agent	8

Overview of Java Agent Installation

The runtime agent protects all applications running under a supported Java Runtime Environment (JRE) on a supported application server or service.

Note: If you need to protect a particular subset of applications, you must run that subset under its own JVM.

To install the runtime agent and add it to an application server or service, follow these steps:

Step	Description	Instructions
1.	Ensure that your target application runs on supported versions of Java Runtime Environment (JRE) and the application server or service.	See the Fortify WebInspect Agent Requirements section in the <i>Micro Focus Fortify System Requirements</i> document for this release.
2.	Install the Java agent.	"Installing the Java Agent" below
3.	Add the agent to an application server or service.	"Adding the Agent to an Application Server or Service Running Java" on page 10
4.	Restart the application server and view the new agent.	"Verifying the Java Agent Installation" on page 22

Installing the Java Agent

Important:

- The agent must have the same permissions on the computer as the user who is responsible for starting the application server.
- Fortify recommends that you install the agent in a secure directory having limited access on your computer or in a subdirectory of the application server. If you use a WebSphere server, make sure the directory path does not contain any spaces.

To install the agent:

1. Copy the agent installation file to the computer on which you are going to install the agent.

Where `xx.x` represents the Runtime version number:

- For UNIX or Linux, the file name is
`Fortify_WebInspect_Runtime_Agent_Java_xx.x_Linux.tar.gz`

- For Windows, the file name is
Fortify_WebInspect_Runtime_Agent_Java_xx.x_windows.zip
2. Expand the agent installation file:

- **UNIX or Linux:**

Use the following command:

```
tar -xzf Fortify_WebInspect_Runtime_Agent_Java_xx.x_Linux.tar.gz
```

- **Windows:** Logged in as an administrator, expand the file using unzip software.
By default, the extracted files are installed in a directory named:

```
Fortify_WebInspect_Runtime_Agent_Java_xx.x_Linux
```

Important: The full path to this installation directory is referred to as *<install_dir>* in these instructions.

For example, if the Fortify_WebInspect_Runtime_Agent_Java_xx.x directory is located at C:\, you replace *<install_dir>* with C:\Fortify_WebInspect_Runtime_Agent_Java_xx.x wherever these instructions refer to *<install_dir>*.

Adding the Agent to an Application Server or Service Running Java

The instructions for adding an agent vary depending on the application server or service to which you are adding the agent. The following topics provide instructions for adding the agent to each supported application server or service.

In general, adding the agent to an application server involves adding an appropriate `-javaagent` argument to the server startup.

Topics covered in this section:

Adding the Agent to a Standalone Apache Tomcat Server	10
Adding the Agent to an Apache Tomcat Windows Service	11
Adding the Agent to an IBM WebSphere Server Using the Server Administrative Console	12
Adding the Agent to an IBM WebSphere Server Using wsadmin	13
Adding the Agent to a Red Hat JBoss Server	14
Adding the Agent to an Oracle WebLogic Server	18
Adding the Agent to a System Service	19
Adding the Agent to a Standalone Java Application	20
Adding the Agent to a Host Machine That Has More Than One Protected Application	20

Adding the Agent to a Standalone Apache Tomcat Server

To configure a standalone Apache Tomcat server to start with the agent, perform the steps in this topic if you are doing one of the following:

- Adding the first agent (you are adding the agent to a system that does not already have an agent)
- Adding another agent (the system already has an agent)

If you are adding the agent to a host machine that is running more than one protected application, follow the instructions in ["Adding the Agent to a Host Machine That Has More Than One Protected Application"](#) on page 20.

UNIX or Linux

To add the agent:

1. Open `<Tomcat_home>/bin/catalina.sh`.
2. Do one of the following:
 - To add the first agent, add the following line beneath the `JAVA_OPTS` section and above the `Execute The Requested Command` comment:

```
CATALINA_OPTS="-javaagent:<install_dir>/lib./FortifyAgent.jar  
$CATALINA_OPTS"
```

- To add another agent, add the **-javaagent** startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
CATALINA_OPTS="-javaagent:<install_dir>/lib./FortifyAgent.jar,  
<existing_agent> $CATALINA_OPTS"
```

Windows

To add the agent:

1. Open `<Tomcat_home>\bin\catalina.bat`.
2. Do one of the following:
 - To add the first agent, add the following line beneath the JAVA_OPTS section and above the Execute The Requested Command comment:

```
set CATALINA_OPTS="-javaagent:<install_dir>\lib\FortifyAgent.jar  
%CATALINA_OPTS%"
```

- To add another agent, add the **-javaagent** startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
set CATALINA_OPTS="-javaagent:<install_dir>\lib\FortifyAgent.jar,  
<existing_agent> %CATALINA_OPTS%"
```

Adding the Agent to an Apache Tomcat Windows Service

To configure an Apache Tomcat Windows service to start with the agent, perform the steps in this topic if you are doing one of the following:

- Adding the first agent (you are adding the agent to a system that does not already have an agent)
- Adding another agent (the system already has an agent)

If you are adding the agent to a host machine that is running more than one protected application, follow the instructions in ["Adding the Agent to a Host Machine That Has More Than One Protected Application"](#) on page 20.

To add the agent:

1. Start the Apache Tomcat configuration application. For example, for Apache Tomcat 7, this is `tomcat7w.exe`.

2. Do one of the following:

- To add the first agent, add the following line to the Java Options section under the Java tab:

```
"-javaagent:<install_dir>\lib\FortifyAgent.jar"
```

- To add another agent, add the **-javaagent** startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
"-javaagent:<install_dir>\lib\FortifyAgent.jar, <existing_agent>"
```

Adding the Agent to an IBM WebSphere Server Using the Server Administrative Console

To add the agent to an IBM WebSphere server using the IBM WebSphere administrative console, perform the steps in this topic if you are doing one of the following:

- Adding the first agent (you are adding the agent to a system that does not already have an agent)
- Adding another agent (the system already has an agent)

If you are adding the agent to a host machine that is running more than one protected application, follow the instructions in ["Adding the Agent to a Host Machine That Has More Than One Protected Application" on page 20](#).

UNIX or Linux

To add the agent:

1. On the WebSphere Application Servers page, select the server for which you want to add the agent.
2. Do one of the following:
 - To add the first agent, add the following option to the Generic JVM Arguments section:

```
-javaagent:<install_dir>/lib./FortifyAgent.jar
```

- To add another agent, add the **-javaagent** startup option (shown in bold text below) to the beginning of the option for the existing agent in the Generic JVM Arguments section. For example:

```
-javaagent:<install_dir>/lib./FortifyAgent.jar, <existing_agent>
```

3. If using WebSphere 7 or higher, add the following option to the Generic JVM Arguments section:

```
-Xshareclasses:none
```

Windows

To add the agent:

1. On the WebSphere Application Servers page, select the server for which you want to add the agent.
2. Do one of the following:
 - To add the first agent, add the following option to the Generic JVM Arguments section:

```
-javaagent:<install_dir>\lib\FortifyAgent.jar
```

- To add another agent, add the **-javaagent** startup option (shown in bold text below) to the beginning of the option for the existing agent in the Generic JVM Arguments section. For example:

```
-javaagent:<install_dir>\lib\FortifyAgent.jar, <existing_agent>
```

3. If you are using WebSphere 7 or higher, add the following option to the Generic JVM Arguments section:

```
-Xshareclasses:none
```

Adding the Agent to an IBM WebSphere Server Using wsadmin

To add the agent to an IBM WebSphere server using the IBM WebSphere wsadmin command-line utility:

1. In the *<WebSphere_home>/profiles/AppSrvN/bin* directory, execute the following command:

Note: On UNIX or Linux systems, you must use a forward slash (/) when specifying the path to the wsadmin command-line utility. On Windows, use a backslash (\).

UNIX or Linux

```
wsadmin -conntype none -f <install_dir>/tools/  
websphereJvmSetup.jacl -fortifyHome <install_dir>
```

Windows

```
wsadmin.bat
```

2. If the application server does not have default WebSphere settings, one or more of the following options might need to be added to the `wsadmin` command:

Parameter	Description
<code>-cell</code>	Specifies the WebSphere server's cell
<code>-server</code>	Specifies the WebSphere server's name Default: <code>server1</code>
<code>-node</code>	Specifies the WebSphere server's node name

Adding the Agent to a Red Hat JBoss Server

To configure a Red Hat JBoss server to start with the agent, perform the steps in this topic if you are doing one of the following:

- Adding the first agent (you are adding the agent to a system that does not already have an agent)
- Adding another agent (the system already has an agent)

If you are adding the agent to a host machine that is running more than one protected application, follow the instructions in ["Adding the Agent to a Host Machine That Has More Than One Protected Application" on page 20](#).

This topic contains the following sections:

- ["JBoss 5.2.0 or Lower" below](#)
- ["JBoss 6.0.1 or Higher" on the next page](#)

JBoss 5.2.0 or Lower

Configure JBoss 5.20 or lower to start with the agent.

UNIX or Linux

To add the agent:

1. Open `<JBoss_home>/bin/run.sh`.
2. Do one of the following:
 - To add the first agent, add the following line:

```
JAVA_OPTS="-javaagent:<install_dir>/lib./FortifyAgent.jar $JAVA_OPTS"
```

- To add another agent, add the `-javaagent` startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
JAVA_OPTS="-javaagent:<install_dir>/lib./FortifyAgent.jar,  
<existing_agent> $JAVA_OPTS"
```

Windows

To add the agent:

1. Open `<JBoss_home>\bin\run.bat`.
2. Do one of the following:
 - To add the first agent, add the following line:

```
set JAVA_OPTS="-javaagent:<install_dir>\lib\FortifyAgent.jar %JAVA_  
OPTS%"
```

- To add another agent, add the `-javaagent` startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
set JAVA_OPTS="-javaagent:<install_dir>\lib\FortifyAgent.jar,  
<existing_agent> %JAVA_OPTS%"
```

JBoss 6.0.1 or Higher

Configure JBoss version 6.0.1 or higher to start with the agent.

UNIX or Linux

To add the agent:

1. Open `<JBoss_home>/bin/standalone.sh`.
2. Do one of the following:
 - To add the first agent, add the following lines:

```
JAVA_OPTS="-javaagent:<install_dir>/lib./FortifyAgent.jar $JAVA_OPTS"  
  
PROCESS_CONTROLLER_JAVA_OPTS =  
    "-javaagent:<install_dir>/lib./FortifyAgent.jar  
    $PROCESS_CONTROLLER_JAVA_OPTS"
```

- To add another agent, add the `-javaagent` startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
JAVA_OPTS="-javaagent:<install_dir>/lib./FortifyAgent.jar,  
<existing_agent> $JAVA_OPTS"
```

```
PROCESS_CONTROLLER_JAVA_OPTS =  
"-javaagent:<install_dir>/lib./FortifyAgent.jar,  
<existing_agent> $PROCESS_CONTROLLER_JAVA_OPTS"
```

3. Add the lines described in [step 2](#) to `<JBoss_home>/bin/domain.sh`.
4. Modify the `standalone.conf` file as follows:
 - a. Append the following to the `-Djboss.modules.system.pkgs=org.jboss.byteman` JVM option:

```
,org.jboss.logmanager,com.fortify
```

- b. Add the following JVM options, depending on the version of JBoss. Replace `<JBoss_home>` with the full path to the JBoss home, and replace `<jar_file_version>` with the version of the jar file for your JBoss release.

If the JBoss version is 6.0.1:

```
-Djava.util.logging.manager=org.jboss.logmanager.LogManager  
-Xbootclasspath/p:<JBoss_home>/modules/org/  
jboss/logmanager/main/  
jboss-logmanager-<jar_file_version>.jar
```

If the JBoss version is 6.1.0 or higher:

```
-Djava.util.logging.manager=org.jboss.logmanager.LogManager  
-Xbootclasspath/p:<JBoss_home>/modules/  
system/layers/base/org/jboss/logmanager/main/  
jboss-logmanager-<jar_file_version>.jar
```

For example, if you are running JBoss 6.2.0 and it is located in `/usr/bin/jboss/jboss-eap-6.2`, you add JVM options similar to the following:

```
-Djava.util.logging.manager=org.jboss.logmanager.LogManager  
-Xbootclasspath/p:/usr/bin/jboss/jboss-eap-6.2/modules/  
system/layers/base/org/jboss/logmanager/main/  
jboss-logmanager-1.5.1.Final-redhat-1.jar
```

- -
 -
 -
 5. Perform the procedures of [step 4](#) for `domain.conf`.

Windows

To add the agent:

1. Open `<JBoss_home>\bin\standalone.bat`.
2. Do one of the following:
 - To add the first agent, add the following lines:

```
set JAVA_OPTS="-javaagent:<install_dir>\lib\FortifyAgent.jar
%JAVA_OPTS%"

set PROCESS_CONTROLLER_JAVA_OPTS =
"-javaagent:<install_dir>\lib\FortifyAgent.jar
%PROCESS_CONTROLLER_JAVA_OPTS%"
```

- To add another agent, add the `-javaagent` startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
set JAVA_OPTS="-javaagent:<install_dir>\lib\FortifyAgent.jar,
<existing_agent> %JAVA_OPTS%"

set PROCESS_CONTROLLER_JAVA_OPTS =
"-javaagent:<install_dir>\lib\FortifyAgent.jar,
<existing_agent> %PROCESS_CONTROLLER_JAVA_OPTS%"
```

3. Add the lines described in [step 2](#) to `<JBoss_home>\bin\domain.bat`.
4. Modify the `standalone.conf.bat` file as follows:
 - a. Append the following to the `-Djboss.modules.system.pkgs=org.jboss.byteman` JVM option:

```
,org.jboss.logmanager,com.fortify
```

- b. Add the following JVM options, depending on the version of JBoss. Replace `<JBoss_home>` with the full path to the JBoss home, and replace `<jar_file_version>` with the version of the jar file for your JBoss release.

If the JBoss version is 6.0.1:

```
-Djava.util.logging.manager=org.jboss.logmanager.LogManager
-Xbootclasspath\p:<JBoss_home>\modules\org\
jboss\logmanager\main\
jboss-logmanager-<jar_file_version>.jar
```

If the JBoss version is 6.1.0 or higher:

```
-Djava.util.logging.manager=org.jboss.logmanager.LogManager  
  
-Xbootclasspath\p:<JBoss_home>\modules\  
  system\layers\base\org\jboss\logmanager\main\  
  jboss-logmanager-<jar_file_version>.jar
```

For example, if you are running JBoss 6.2.0 and it is located in C:\bin\jboss\jboss-eap-6.2, you add JVM options similar to the following:

```
-Djava.util.logging.manager=org.jboss.logmanager.LogManager  
  
-Xbootclasspath\p:C:\bin\jboss\jboss-eap-6.2\modules\  
  system\layers\base\org\jboss\logmanager\main\  
  jboss-logmanager-1.5.1.Final-redhat-1.jar
```

5. Perform the procedures of [step 4](#) for domain.conf.bat.

Adding the Agent to an Oracle WebLogic Server

To configure an Oracle WebLogic server to start with the agent, perform the steps in this topic if you are doing one of the following:

- Adding the first agent (you are adding the agent to a system that does not already have an agent)
- Adding another agent (the system already has an agent)

If you are adding the agent to a host machine that is running more than one protected application, follow the instructions in ["Adding the Agent to a Host Machine That Has More Than One Protected Application"](#) on page 20.

UNIX or Linux

To add the agent:

1. Open <WebLogic_home>/bin/startWebLogic.sh.
2. Do one of the following:
 - To add the first agent, add the following line:

```
JAVA_OPTIONS="-javaagent:<install_dir>/lib./FortifyAgent.jar $JAVA_  
OPTIONS"
```

- To add another agent, add the **-javaagent** startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
JAVA_OPTIONS="-javaagent:<install_dir>/lib./FortifyAgent.jar,  
<existing_agent> $JAVA_OPTIONS"
```

Windows

To add the agent:

1. Open `<WebLogic_home>\bin\startWebLogic.cmd`.
2. Do one of the following:
 - To add the first agent, add the following line:

```
set JAVA_OPTIONS="-javaagent:<install_dir>\lib\FortifyAgent.jar  
%JAVA_OPTIONS%"
```

- To add another agent, add the `-javaagent` startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
set JAVA_OPTIONS="-javaagent:<install_dir>\lib\FortifyAgent.jar,  
<existing_agent> %JAVA_OPTIONS%"
```

Adding the Agent to a System Service

To add runtime agent protection to a Java Virtual Machine (JVM) or application server running as a system service for UNIX, Linux, or Windows, perform the steps in this topic if you are doing one of the following:

- Adding the first agent (you are adding the agent to a system that does not already have an agent)
- Adding another agent (the system already has an agent)

If you are adding the agent to a host machine that is running more than one protected application, follow the instructions in ["Adding the Agent to a Host Machine That Has More Than One Protected Application" on the next page](#).

UNIX, Linux, and Windows

Incorporate the following parameter into the script that starts the JVM or application server for the system service:

Note: On Windows systems, replace the forward slashes (/) in the following paths with backslashes (\).

- To add the first agent, add the following line:

```
"-javaagent:<install_dir>/lib./FortifyAgent.jar"
```

- To add another agent, add the **-javaagent** startup option (shown in bold text below) to the beginning of the option for the existing agent in the Java Options section under the Java tab. For example:

```
"-javaagent:<install_dir>/lib./FortifyAgent.jar,  
  <existing_agent>"
```

Adding the Agent to a Standalone Java Application

To configure a standalone Java application to start with the agent, perform the steps in this topic if you are doing one of the following:

- Adding the first agent (you are adding the agent to a system that does not already have an agent)
- Adding another agent (the system already has an agent)

If you are adding the agent to a host machine that is running more than one protected application, follow the instructions in ["Adding the Agent to a Host Machine That Has More Than One Protected Application"](#) below.

UNIX, Linux, and Windows

Note: On Windows systems, replace the forward slashes (/) in the following paths with backslashes (\).

- To add the first agent, add the following parameter to the application's execution command:

```
"-javaagent:<install_dir>/lib./FortifyAgent.jar"
```

For example:

```
java "-javaagent:<install_dir>/lib./FortifyAgent.jar  
  <other_java_parameters> <application_name>"
```

- To add another agent, add the **-javaagent** startup option (shown in bold text below) to the beginning of the option for the existing agent. For example:

```
java "-javaagent:<install_dir>/lib./FortifyAgent.jar, <existing_agent>  
  <other_java_parameters> <application_name>"
```

Adding the Agent to a Host Machine That Has More Than One Protected Application

Note: If you are adding the agent to a system that has (or will have) only one protected application, follow the instructions for the application server or service to which you are adding the agent. See ["Adding the Agent to an Application Server or Service Running Java"](#)

on page 10.

If you have more than one protected application running on the same host machine, perform the following steps to add the agent to the application server or service.

UNIX, Linux, and Windows

To add the agent:

Note: On Windows systems, replace the forward slashes (/) in the following paths with backslashes (\).

1. For each protected application, you must create a unique agent configuration file. Do this by copying the `<install_dir>/config/rt_config.xml` file into the same directory with an application-appropriate name, such as `myapp1_config.xml`.
2. In the new file, change the `ProgramName` setting from `default` to the name of the application. For example, in `<install_dir>/config/myapp1_config.xml`, change the `ProgramName` setting from `default` to `myapp1`.
3. For each application server or service, add the new configuration file to the appropriate `-javaagent` startup option (shown in bold text below) as follows:
 - To add the first agent, add the following line:

```
"-javaagent:<install_dir>/lib./FortifyAgent.jar"
```

For example:

```
"-javaagent:<install_dir>/lib./FortifyAgent.jar=  
<install_dir>/config/myapp1_config.xml"
```

- To add another agent, add the `-javaagent` startup option to the beginning of the option for the existing agent:

```
"-javaagent:<install_dir>/lib./FortifyAgent.jar,  
<existing_agent>"
```

For example, if you are adding an agent to an application server or service that does not already have an installed agent, you add the following:

```
"-javaagent:<install_dir>/lib./FortifyAgent.jar=  
<install_dir>/config/myapp1_config.xml, <existing_agent>"
```

Verifying the Java Agent Installation

Topics covered in this section:

Troubleshooting Tips for the Java Agent	22
Uninstalling a Java Agent	22

Troubleshooting Tips for the Java Agent

A new agent does not appear

If, after restarting the application server, the new agent does not appear as described in [Restarting the Application Server and Viewing the New Java Agent](#), check the agent's log file for errors as follows:

1. In the log file
`<install_dir>/log/system.log` for UNIX or Linux
or
`<install_dir>\log\system.log` for Windows
look for a message similar to the following:

```
[<PID> <TIMESTAMP> INFO] Micro Focus Fortify Runtime setup  
complete
```

2. Ensure that the timestamp on the message corresponds to the time that the application server was started. Also ensure that there are no messages in the log with the prefix ERROR or FATAL.

The log file does not exist or application server startup messages are not present

If the log file does not exist or if messages that correspond to the application server startup time are not present, it indicates that the agent is not running. Take the following steps to identify the issue:

1. Make sure the startup arguments that you modified earlier are correct.
2. Check the `stderr` output from the application server or service for any fatal configuration errors.

Uninstalling a Java Agent

To uninstall a runtime agent for Java and remove the agent from your system:

1. To deactivate Runtime, undo any startup script changes that you made.
2. Delete `<install_dir>`.

Installing the .NET Agent

Topics covered in this section:

Getting Started with the .NET Agent Installation	23
Overview of .NET Agent Installation	23
Installing the .NET Agent	24
Silent Install	25
Verifying the .NET Agent Installation	25
Restarting IIS and Viewing the New .NET Agent	25
Troubleshooting Tips for the .NET Agent	26
Uninstalling a .NET Agent	26
Restarting IIS and Viewing the New .NET Agent	26

Getting Started with the .NET Agent Installation

Topics covered in this section:

Overview of .NET Agent Installation	23
Installing the .NET Agent	24
Silent Install	25

Overview of .NET Agent Installation

The runtime agent protects all applications running under a supported .NET Framework on a supported version of IIS.

Note: If you need to protect a particular subset of applications, you must configure that subset as an application pool and protect that application pool.

Note: If you are upgrading a previous installation of a .NET agent, you must install the new agent without uninstalling the old agent, to preserve your protection settings.

To install the runtime agent and add it to IIS, follow these steps:

Step	Description	Instructions
1.	Ensure that your target application runs on supported versions of .NET Framework and IIS.	See the Fortify WebInspect Agent Requirements section in the <i>Micro Focus Fortify System Requirements</i> document for this release.
2.	Run the agent installer.	"Installing the .NET Agent" below
3.	Restart IIS and view the new agent.	"Verifying the .NET Agent Installation" on the next page

Installing the .NET Agent

Important:

- The agent must have the same permissions on the computer as the user who is responsible for starting IIS.
- Fortify recommends that you install the agent in a secure directory having limited access on your computer.

To install the agent:

1. Copy the agent installation file to the computer on which you are going to install the agent, if the file was downloaded to a different computer.

Where *xx.x* represents the Runtime version number:

- For 64-bit Windows, the file name is
Fortify_WebInspect_Runtime_Agent_Dotnet_xx.x.windows_x64.exe
- For 32-bit Windows, the file name is
Fortify_WebInspect_Runtime_Agent_Dotnet_xx.x_windows_x86.exe

2. Run the installer from the directory where the extracted files are stored.

By default, the installer places the files in the following directory:

`<install_dir>\WebInspect_RuntimeAgt_Dotnet_xx.x`

but you can use a different location. These instructions assume that you use the default location.

Important: The full path to this installation directory is referred to as `<install_dir>` in these instructions.

For example, if the `WebInspect_RuntimeAgt_Dotnet_xx.x` directory is located at `C:\`, you replace `<install_dir>` with `C:\WebInspect_RuntimeAgt_Dotnet_xx.x` wherever these instructions refer to `<install_dir>`.

Silent Install

You can streamline the .NET installation process with a silent installation. To install the .NET agent from the command line:

- Run the installation .exe file from the command line with the option `--mode unattended`.
or
- Run the installation .exe file from the command line with the option `--help` to access a list of options.

Verifying the .NET Agent Installation

Topics covered in this section:

Restarting IIS and Viewing the New .NET Agent	25
Troubleshooting Tips for the .NET Agent	26
Uninstalling a .NET Agent	26

Restarting IIS and Viewing the New .NET Agent

To restart IIS and view the new agent:

1. As an administrative user, execute the following command to activate Runtime:

```
<install_dir>\WebInspect_RuntimeAgt_Dotnet_xx.x\  
tools\IISControl.exe register restart
```

Note: If you need to protect a particular subset of applications on the server, configure that subset as an application pool and add

`-a <application pool name>` to the command. For example:

```
<install_dir>\WebInspect_RuntimeAgt_Dotnet_xx.x\  
tools\IISControl.exe -a MyAppPool register restart
```

2. .NET requires that you open your application from a browser. When you do so, IIS starts both the application and Runtime.
3. After the server has started, make sure the new agent appears:
 - a. Start WebInspect.
 - b. Start a scan.
 - c. In the Scan Dashboard page, verify that in the **Scan** section in the right pane, the **Agent** field is displayed as **Detected**.
 - d. If the new agent is not operating as described above, see "[Troubleshooting Tips for the .NET Agent](#)" on the next page.

Troubleshooting Tips for the .NET Agent

A new agent does not appear

If, after restarting IIS, the new agent does not appear as described in ["Restarting IIS and Viewing the New .NET Agent" below](#), check the agent's log file for errors as follows:

1. In the log file

```
<install_dir>\WebInspect_RuntimeAgt_Dotnet_xx.x\  
log\system.log
```

look for a message similar to the following:

```
[<PID> <TIMESTAMP> INFO] Micro Focus Fortify Runtime setup  
complete
```

2. Ensure that the timestamp on the message corresponds to the time that IIS was started. Also ensure that there are no messages in the log with the prefix ERROR or FATAL.

The log file does not exist or IIS startup messages are not present

If the log file does not exist or if messages that correspond to the IIS startup time are not present, it indicates that the agent is not running. In this case, see whether an error has been reported in the Windows system event log.

Uninstalling a .NET Agent

To deactivate a .NET runtime agent and remove the agent from your system:

1. As an administrative user, execute the following command:

```
<install_dir>\WebInspect_RuntimeAgt_Dotnet_xx.x\  
tools\IISControl.exe unregister restart
```

2. Select **Control Panel > Programs and Features**.
3. Right-click **Fortify WebInspect Runtime Agent Dotnet xx.x** where **xx.x** represents the version number, and perform the uninstall.

Restarting IIS and Viewing the New .NET Agent

To restart IIS and view the new agent:

1. As an administrative user, execute the following command to activate Runtime:

```
<install_dir>\WebInspect_RuntimeAgt_Dotnet_xx.x\  
tools\IISControl.exe register restart
```

Note: If you need to protect a particular subset of applications on the server, configure that subset as an application pool and add `-a <application pool name>` to the command. For example:

```
<install_dir>\WebInspect_RuntimeAgt_Dotnet_xx.x\  
tools\IISControl.exe -a MyAppPool register restart
```

2. .NET requires that you open your application from a browser. When you do so, IIS starts both the application and Runtime.
3. After the server has started, make sure the new agent appears:
 - a. Start WebInspect.
 - b. Start a scan.
 - c. In the Scan Dashboard page, verify that in the **Scan** section in the right pane, the **Agent** field is displayed as **Detected**.
 - d. If the new agent is not operating as described above, see ["Troubleshooting Tips for the .NET Agent" on the previous page](#).

Send Documentation Feedback

If you have comments about this document, you can [contact the documentation team](#) by email. If an email client is configured on this computer, click the link above and an email window opens with the following information in the subject line:

Feedback on Installation Guide (Fortify WebInspect Agent 20.1.0)

Just add your feedback to the email and click send.

If no email client is available, copy the information above to a new message in a web mail client, and send your feedback to FortifyDocTeam@microfocus.com.

We appreciate your feedback!